



Sycaps



Proximity Time & Attendance Terminals

Computerize to increase accuracy and efficiency

Card capacity maximum of 250 cards

High speed digital conversion and classification (1:N).

Maximum 4,200 transaction records storage when in stand-alone mode

Easy to use, simple Plug & Play USB port. No

additional configuration required.

Multi-language support option available

Suitable for many different field of company

Dimensions: 135W x 195H x 90D

Technical Specifications :

Frequency	125KHz		13.56MHz
Card(Transponder) Read range*	SYRIS card (EM/Temic Compatible) 2cm~10cm		Mifare series 2cm~8cm
Number of user	250 users		
Capacity of records Output interface	USB Port 4,200 records		
Input points Baud rate	Normally 4 Data Input Points 19,200bps (4,800bps~230,400bps)		
Speaker output	Speaker built-in Maximum 0.2W		
Bell	16 sets of timer Active time 1 sec ~ 250 sec		
Indicator	3 LED		
Keypad	4 metal keypad with backlight		
LCD display	128 x 64 Dot (16 x 4 Char) LCD with Backlight		
Tamper switch	Built-in		
Language	Language (English)		
Support Software Power consumption	SYCAPS T&A Management System 0.5W to 2W		
Power supply / TEMP.	USB or/and 7V to 9V DC -20 to 55 / -30 to 70		